< 滁州惠盛电子材料有阻公司

Chuzhou Hui-Sheng Electronic Materials Co., Ltd.

Co. Whi: http://www.hs-epoxy.com

Wh2: http://www.epoxy-c.com/

1

MATERIAL SAFTY DATA SHEET (MSDS) 1008A/1008B

1.a) PRODUCT 1008A

1.b) SUPPLIER

Tel.:

Company: Chuzhou Hui-Sheng Electronic Materials Co., Ltd.

Address: Chuzhou City, Anhui Province, south of Science and Technology Industrial Park, Wan Lian Road NO.2

+86-550-3213188 Fax : +86-550-3213188

2. COMPOSITION AND INFORMATION ON INGREDIENTS

BPA type epoxy resin & Filler

3. HAZARDS IDENTIFICATION

Acute health effects: none

Potential chronic health effects: no relevant information found

Main symptom: obtain subtance mightly causing variation. May cause sensitization by skin contact.

4. FIRST AID MEASURES

Inhalation: remove the victim from the contamination immediately to fresh air.

Skin contact: wash the affect area under warm running water with a mild soap for 20 mins.

Hazardous skin contact: medical treatment as soon as possible.

Eye contact: rinse the affected eyes with clean water for at least 15 minutes, and then seek medical treatment.

Ingestion: seek medical treatment

5. FIRE AND EXPLOSION DATA

Fire Fighting Media and instructions: dry chemical powder, carbon dioxide or dry sand

6. ACCIDENTAL RELEASE MEASURES

Dress personal protecting equipment.

Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste

container with covers for disposal. Don't put this product into the river to avoid pollution.

7. HANDLING AND STORAGE

Handling: Wear proper protective equipment. Avoid contact with skin or eyes. Avoid steam and liuid to give out.

8. PHYSICAL AND CHEMICAL PROPERTIES

Physical state and appearanceblack or gray ropy liquidOdourcharacteristic odorBoiling pointnot availableDensity1.1~1.3g/mlSolubility in waterinsolublemay viald earbon monovide and earbon dioxide and hydrochloria a

may yield carbon monoxide and carbon dioxide and hydrochloric acid.

< 滁州惠盛电子材料有阻公司

🖊 Chuzhou Hui-Sheng Electronic Materials Co., Ltd.

PRODUCT 1.a)

Tel.:

SUPPLIER

1008B

1.b)

Company: Chuzhou Hui-Sheng Electronic Materials Co., Ltd.

Address: Chuzhou City, Anhui Province, south of Science and Technology Industrial Park, Wan Lian Road NO.2

+86-550-3213188Fax : +86-550-3213188

2. **COMPOSITION AND INFORMATION ON INGREDIENTS** Modified amine & Filler

3. **HAZARDS IDENTIFICATION**

Acute health effects: none

Potential chronic health effects: no relevant information found

Main symptom: obtain subtance mightly causing variation. May cause sensitization by skin contact.

4. FIRST AID MEASURES

Inhalation: remove the victim from the contamination immediately to fresh air. Skin contact: wash the affect area under warm running water with a mild soap for 20 mins.

Hazardous skin contact: medical treatment as soon as possible.

Eye contact: rinse the affected eyes with clean water for at least 15 minutes, and then seek medical treatment.

Ingestion: seek medical treatment

FIRE AND EXPLOSION DATA 5.

Fire Fighting Media and instructions: dry chemical powder, carbon dioxide or dry sand

6. **ACCIDENTAL RELEASE MEASURES**

Dress personal protecting equipment.

Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste

container with covers for disposal. Don't put this product into the river to avoid pollution.

7. HANDLING AND STORAGE

Handling: Wear proper protective equipment. Avoid contact with skin or eyes. Avoid steam and liuid to give out.

8. PHYSICAL AND CHEMICAL PROPERTIES

Physical state and appearance	brown ropy liquid
Odour	characteristic odor
Boiling point	not available
Density	1.1~1.3g/ml
Solubility in water	insoluble
may yield carbon monoyide and carbon dioyide and hydrochlori	

may yield carbon monoxide and carbon dioxide and hydrochloric acid.

2